



Technomed understands the importance of a crystal clear signal, ease of use and good grounding.

Technomed's Monopolar Needle Electrode - trocar point and cable solutions are designed for optimal sharpness and ease of use.


The hub and cable provide a firm grip and optimal precision in needle positioning.

User Benefits

- Clear and reliable signal with improved recording
 area.
- Ease of penetration and repositioning with sharper needle tip
- Precise handling with improved ergonomic hub and cable design
- Approved for stimulation
- Optional shielded cable for 50/60 Hz interference elimination

Available variants

| Product Description | Needle Length | Diameter | Hub Color | Part Number |
|------------------------|------------------|--------------------|--------------|------------------|
| Pre-wired | 25 mm | 0.35 mm (28 Gauge) | Red | TE/AP2535-335/01 |
| Pre-wired | 25 mm | 0.45 mm (26 Gauge) | Yellow | TE/AP2545-335/01 |
| Pre-wired | 37 mm | 0.35 mm (28 Gauge) | Orange | TE/AP3735-335/01 |
| Pre-wired | 37 mm | 0.45 mm (26 Gauge) | Green | TE/AP3745-335/01 |
| Pre-wired | 50 mm | 0.45 mm (26 Gauge) | Blue | TE/AP5045-335/01 |
| Pre-wired | 75 mm | 0.45 mm (26 Gauge) | Violet | TE/AP7545-335/01 |
| Detachable | 25 mm | 0.35 mm (28 Gauge) | Red | TE/AD2535-008/01 |
| Detachable | 25 mm | 0.45 mm (26 Gauge) | Yellow | TE/AD2545-008/01 |
| Detachable | 37 mm | 0.35 mm (28 Gauge) | Orange | TE/AD3735-008/01 |
| Detachable | 37 mm | 0.45 mm (26 Gauge) | Green | TE/AD3745-008/01 |
| Detachable | 50 mm | 0.45 mm (26 Gauge) | Blue | TE/AD5045-008/01 |
| Detachable | 75 mm | 0.45 mm (26 Gauge) | Violet | TE/AD7545-008/01 |



Packing: 25 individually packed electrodes per box

Pre-wired: 0.75 m

| Reusable Cable | Wire Length | Part Number |
|----------------|-------------|-------------|
| Shielded | 1 m | TE/D54-451 |
| Unshielded | 0.6 m | TE/D34-231 |

Specifications

| Lead-free | | |
|---------------------------------|-------------------|--|
| Latex-free | √ | |
| BPA-free | \checkmark | |
| DEHP < 0.1% by weight | \checkmark | |
| REACH & RoHS compliant | √ | |
| EtO sterilized | √ | |
| Lead wire core | Tin Plated Copper | |
| Lead wire insulation | PVC | |
| Connector | DIN 42802 | |
| Shelf life for unopened pouches | 36 months | |



Your Technomed Business Partner:



USA Rx ONLY





Technomed

Amerikalaan 71 6199 AE | Maastricht-Airport | The Netherlands T +31 43 408 68 68 | info@technomed.nl

Technomed USA

Suite 4990 Constellation Drive
White Bear Township | MN 55127 | United States
T +1 651 288 0890 | info@technomed-usa.com

www.technomed.nl